

BIOTOOL SWISS

innovative laboratory technology



Spray protector



Flame shield



Bracket stand



Safety adapter

LabFlame IR

LabFlame +



LabFlame IR A laboratory bunsen burner with touch-free ignition capability for enhanced safety

LabFlame + Modelled on the LabFlame IR with an additional battery slot to allow cordless operation

RAPID & PRECISE IGNITION

for fastest loop sterilization

UNIFORM & CONSTANT FLAME

enables perfect bottle neck sterilization

SAFETY CABINET QUALIFIED

due to optimized air flow support

HANDS FREE OPERATION

can be operated by a foot switch or touch free IR-sensor ignition

The new LabFlame has been designed specifically for use in microbiology laboratories. The one-piece, stainless steel housing is free from any gaps or rims and therefore easy to clean and fully UV resistant. Its optimized air-flow system allows a uniform and constant flame even in safety cabinets with horizontal or vertical air flow. LabFlame can be connected to any gas source. All controls for gas and air supply, as well as the multifunctional control for the modes of operation, are conveniently located on the easy to read display.

When safety matters ...

LabFlame automatically cuts the gas supply when the flame is extinguished and checks the burner head temperature.

When gas consumption matters ...

LabFlame cuts the gas after each loop sterilization and LabFlame starts straight-away with an optimal flame shape.

ALWAYS READY – FULL METAL BODY – A JEWEL ON YOUR LAB BENCH

Really fast

Super fast flame ignition & high precision gas mix

Without grooves and rough edges

The low profile body facilitates lab-ergonomic operation; the streamlined design reduces air flow disturbances in a clean room workbench to a minimum. Moreover the LabFlame is very easy to clean – a laboratory gas burner without grooves and rough edges.

Superior safety features

LabFlame constantly analyzes potential hazards and initiates automatic interruption of the gas supply. It offers a continuous burner head control (BHC) and overheating protection. BHC unfailingly identifies burner head clogging by liquids or solid substances and ensures the correct assembly of the burner head!

After prolonged use, the residual heat display will signal that the burner head is still hot in order to protect the user from burns.

The adjustable automatic cut-off system inhibits unintentional ignition when the flame has not been ignited for a longer period of time.



MODES Foot switch / Pedal

Pedal I	Push button mode
Pedal II	Start/Stop + exact time set (sec.)

MODES IR Sensor

Sensor I	Auto-Off mode with time set
Sensor II	Start/Stop + exact time set (sec.) Residual burning time displayed

SETTINGS Safety & Commodity

BHC	Burner head control
Sensor	Click or DoubleClick start
Stand-by	Automatic switch off setting
IR-Sensor	Sensitivity range setting -III+
Language	EN - DE - FR - SP

TECHNICAL DATA

Flame temp.:	1350°C on liquid gas 1300°C on natural gas
Temp. threshold level:	1.2 kW liquid gas 1.0 kW natural gas
Housing:	Stainless steel / glass UV and solvent resistant
Burner head:	Stainless steel
Cover of burner shaft:	Ø 23 mm, with drains
Dimension (w x h x d):	103 x 49 x 130 mm
Weight:	700g

SAFETY APPROVED!



Item No.

LF8.000.000 LabFlame IR DoubleClick IR-sensor (adjustable), turbo flame ignition, **Safety Control System (SCS)**, **Burner Head Control (BHC)**, removable burner head, 2 nozzles for natural gas and propane/butane gas, wrench 17mm for gas connection, tubing connector with swivel nut, switching power supply (global), optional foot switch.

LF8.002.000 LabFlame + All LabFlame IR components + additional slot for rechargeable battery pack. For cable free operation in biological safety cabinets (option 800900 required)

Accessories

Flame shield



8000600

Spray protector



6000200 Standard
6000210 Autoloop

Loop tray



8000340 For 3 loops
connectable right/left side

Life science head



8100090 Regular head
8100091 Life science
burner head (double height)

Foot switch / Pedal



8000402 Stainless steel
6000403 Mini / benchtop
both pedals with power cord

AutoLoop



8000380 AutoLoop for
LabFlame IR / Lab Flame +

Safety adapter CV 360



8000700 Side / compact
8000750 Rear / slim
safety adapter with pressure
regulator and 1 gas nozzle

Safety adapter CV 470



6000855 Base plate
6000850 Safety adapter
with pressure regulator

Safety adapter CV 206



6000800 Safety adapter
with pressure regulator

Safety adapter CP 250



6000820 Safety adapter
with pressure regulator

Battery charger kit



8000900 For LabFlame +
with 2 battery packs (LI-ION)
rechargeable

NOVA Microincinerator



AG.S3022 Electrical 220 V
gas-free loop neutralizing for the
use in laminar flow cabinets

VITARIS
A Difference in Life Science

VITARIS AG
Blegistrasse 9
CH-6340 Baar

Tel.: 041 769 00 00
Fax: 041 769 00 01
E-mail: info@vitaris.com

www.vitaris.com